



AquaTek™



The Orca™ nozzle allows you to connect two jetter units and receive double the water flow.

## ORCA™ Nozzle

To clean larger pipes cost effectively there is a demand of higher flow nozzles. This is the reason why we have developed the Orca™ nozzle which allows you to connect two jetter units and receive double the water flow.

### Characteristics & Construction:

- Quality stainless steel construction with conduits that allow turbulence free water transportation to the individual jet with SBR rubber conduit cover. This allows for a jet stream to be maintained longer and farther down the pipe.
- Variable jet sizes to accommodate flows from 200 up to 1500 l/min (60-400 US GPM).
- Low angle jet stream, attacks debris at its weakest point with superior performance.
- One swivel needed for mounting and operation



Specifications	
Hose size	Two separate hoses (any standard size) are required
Flow rates	200 – 1500 l/min (60-400 US GPM)
Pipe size	15" and up
Jet sizes	1,9 mm to 6,0 mm
Sled sizes	One none adjustable
Weight does not include swivel	4,7 kg (10 lbs)
Length	470 mm (18,5 ")
Diameter	290 mm (11,4")

*Note: Weights and dimensions are approximate and subject to change without notice.*

Art no.	Description
BLT-25	The Orca™ nozzle incl. 8 jets, 1 stainless steel swivel. Connection 1" BSP female thread.
BLT-32	The Orca™ nozzle incl. 8 jets, 1 stainless steel swivel. Connection 1 1/4" BSP female thread.

