



AquaTek™



NATAB™ is an improvement of the predecessor to the Predator series.

NATAB™ / GOBLIN™

NATAB™ was the predecessor to the BL series which include the Jaws® and Hammerhead™. They both became revolutionary in the market and are widely used today all over the world. Since then we have improved the NATAB™ Nozzle.

NATAB™ has water bearing walls to ensure smooth water streams with less turbulence. By this construction the water's energy is kept until it becomes useful for cleaning the pipes. NATAB™ is about twice as effective as conventional nozzles with drilled interior.

We know that our nozzles have been used for copying, but if you don't have the knowledge about cooperating factors such as flow rates, pressure and design of nozzles, you will not succeed.

NATAB™ has 10 exchangeable jets; half of them with 30 degrees angle and the other half with 15 degrees, to fit customers flush pumps and hose dimensions. The jets used on the Jaws® Nozzle is also used on NATAB™. There is also a front hole, which can be plugged when not in use.

NATAB™ is made in quality stainless steel.



AquaTeq™



Specifications NATAB™	
Hose size	3/4" up to 1 1/4"
Flow rate	100 – 1000 l/min (30-250 US GPM)
Pipe size	Ø 6" and up, Ø 150 mm and up
No. of jets	10 + 1
Jet size	1,9 - 6,0 mm
Weight	5,5 kg (12lbs)
Length	190 mm (7 1/2")
Diameter	98 mm (4")

Note: Weights and dimensions are approximate and subjects to change without notice.

Art no.	Description
BLN-25	NATAB™ incl. 10+2 jets. 1" female hose connection BSP or NPT.
BLN-32	NATAB™ incl. 10+2 jets. 1 1/4" female hose connection BSP or NPT.
BLNWB-25	NATAB™ incl. 10+2 jets and one wear body. 1" female hose connection BSP or NPT.
BLNWB-32	NATAB™ incl. 10+2 jets and one wear body. 1 1/4" female hose connection BSP or NPT.