



# AquaTeq™



**NATAB™** is an improvement of the predecessor to the Predator series.

## NATAB™ / GOBLIN™

NATAB™ was the predecessor to the BL series which include the Jaws® and Hammerhead™. They both became revolutionary in the market and are widely used today all over the world. Since then we have improved the NATAB™ Nozzle.

NATAB™ has water bearing walls to ensure smooth water streams with less turbulence. By this construction the water's energy is kept until it becomes useful for cleaning the pipes. NATAB™ is about twice as effective as conventional nozzles with drilled interior.

We know that our nozzles have been used for copying, but if you don't have the knowledge about cooperating factors such as flow rates, pressure and design of nozzles, you will not succeed.

NATAB™ S has 4 exchangeable thrusting jets and one front jet, which can be plugged when not used. The jet system is the same as for the Hammerhead® nozzle. NATAB™ S is made in bronze.

NATAB™ L has 10 exchangeable thrusting jets; half of them with 30 degrees angle and the other half with 15 degrees, to fit customer's flush pumps and hose dimensions. There is also a front jet, which can be plugged when not used. NATAB™ L uses the same jet system as the Jaws® Nozzle. NATAB™ L is made in quality stainless steel.

**AquaTeq Sweden AB** ADDRESS Kalmar Tech Park, SE-393 56 KALMAR

PHONE +46 (0)480 270 10 FAX +46 (0)480 125 80

EMAIL [info@aquateq.com](mailto:info@aquateq.com) HOMEPAGE [www.aquateq.com](http://www.aquateq.com)



| Specifications NATAB™ S |   |
|-------------------------|---|
| Hose size               | 3/8" , 1/2" and 3/4"                            |
| Flow rate               | 15 – 200 l/min (4-50 US GPM)                    |
| Pipe size               | Ø 100 mm up to 300 mm                           |
| No. of jets             | 4 + 1   |
| Jet size                | 0,9 up to 2,8 mm                                |
| Weight                  | 0,5 kg (1,1 Lbs.) (with sled 0,8 kg (1,8 Lbs.)) |
| Length                  | 70 mm (3")                                      |
| Diameter                | 50 mm (2")                                      |

*Note: Weights and dimensions are approximate and subjects to change without notice.*

| Art no.    | Description                           |
|------------|---------------------------------------|
| 2-11355    | NATAB exkl. 5 x jets, 1/2" connection |
| 2-13350-13 | Sled 1/2", Ø 100 mm                   |
| 2-13350-19 | Sled 3/4", Ø 100 mm                   |
| 2-13351-13 | Sled 1/2", Ø 150 mm                   |
| 2-13351-19 | Sled 3/4", Ø 150 mm                   |
| 2-12360-   | Steel Jet                             |



| Specifications NATAB™ L |                                  |
|-------------------------|----------------------------------|
| Hose size               | 3/4" up to 1 1/4"                |
| Flow rate               | 100 – 1000 l/min (30-250 US GPM) |
| Pipe size               | Ø 6" and up, Ø 150 mm and up     |
| No. of jets             | 10 + 1                           |
| Jet size                | 1,9 - 6,0 mm                     |
| Weight                  | 5,5 kg (12lbs)                   |
| Length                  | 190 mm (7 1/2")                  |
| Diameter                | 98 mm (4")                       |

*Note: Weights and dimensions are approximate and subjects to change without notice.*

| Art no.    | Description                              |
|------------|--|
| 2-11650    | NATAB exkl. 12 x jets, 1 1/4" connection |
| 2-11650-WB | Wear body NATAB 1 1/4"                   |
| 2-12660-   | Steel Jet                                |
| 2-12661-   | Ceramic Jet                              |