



AquaTeq™



The Spinner™ series are developed for a flexible and effective removal of grease, smoother deposits, smaller roots etc.

SPINNER™

The Spinner™ series are developed for a flexible and effective removal of grease, smoother deposits, smaller roots etc. They have thrusting jets that are changeable according to your specifications, together with rotating adaptable propulsion 90° and 45° jets. With this you will get a strong water pattern for effective removal of debris.

The closer the jet is towards the debris the more effective it becomes. This is probably the most important rule when using a spinning (rotating) nozzle.

In our assortment we also have rotating nozzle from 1/8" and up.

Characteristics:

- Quality stainless steel and brass construction
- Variable jet sizes to accommodate flows from 40 up to 1000 l/min (25-265 US GPM).
- Low jet angle for maximum thrusting power.



Specifications Spinner 1/2"

| | |
|----------------|-------------------------------------|
| Hose size | 1/2" |
| Water flow | 40 – 200 l/min (10-50 US GPM) |
| Pipe dimension | Ø 75 mm up to 250 mm (3" up to 10") |
| No. of jets | 4 thrust jets, 4+2 rot.jets |
| Jet size | 0,8 up to 2,8 mm |
| Weight | 0,7 kg (1,5 Lbs.) |
| Length | 78 mm (3,1") |
| Diameter | 44 mm (1,7") |

Note: Weights and dimensions are approximate and subject to change without notice.

Article list

| Art no. | Description |
|---------|--|
| 2-11380 | BL SPINNER excl. 10 x jets 1/2" connection |



Specifications Spinner 1"

| | |
|----------------|---------------------------------|
| Hose size | 3/4" and 1" |
| Water flow | 100 - 400 l/min (25-105 US GPM) |
| Pipe dimension | Ø 100 mm up to 400 mm |
| No. of jets | 6 thrust jets, 4+4 rot. jets |
| Jet size | 0,9 mm up to 2,8 mm |
| Weight | 1,9 kg (4,2 Lbs.) |
| Length | 110 mm (4,4") |
| Diameter | 67 mm (2,7") |

Note: Weights and dimensions are approximate and subject to change without notice.

Article list

| Art no. | Description |
|---------|---|
| 2-11580 | BL SPINNER excl. 14 x jets, 1" connection |



Specifications Spinner 1 1/4"

| | |
|----------------|-----------------------------------|
| Hose size | 1" and 1 1/4" |
| Water flow | 100 – 1000 l/min (25-265 US GPM) |
| Pipe dimension | Ø 150 up to 500 mm (6" up to 20") |
| No. of jets | 6 thrust jets, 4+4 rot.jets |
| Jet size | 0,9 up to 6,0 mm |
| Weight | 5,2 kg (11,5 Lbs.) |
| Length | 157 mm (6,2") |
| Diameter | 88 mm (3,5") |

Note: Weights and dimensions are approximate and subject to change without notice.

Article list

| Art no. | Description |
|---------|--|
| 2-11680 | BL SPINNER excl. 14x jets 1 1/4" connection |
| 2-13680 | Sled BL SPINNER 1 1/4" Ø 225 mm with counterweight |
| 2-13681 | Sled BL SPINNER 1 1/4" Ø 225 mm short with counterweight |