

STÄLLBAR SLÄDE TILL LUMBERJACK® LJ300

Lumberjack® modell LJ300 har nu kompletterats med två ställbara slädar som enkelt justeras efter rördimension.

Den mindre släden används i rör med innerdiameter från 200 upp till 375 mm och stora släden från 400 till 700 mm.

Slädarna är utrustade med utbytbara hjul för lättare framdrift och enkel service.

Till stora släden (400-700 mm) är framtaget en expanderplatta som minskar kättinglängden och därmed ökar effektiviteten. Se separat information "Expanderplatta för LJ300".

För att ytterligare stabilisera den stora släden i rör kan den kompletteras med förlängningsmedar.



ADJUSTABLE SLED FOR LUMBERJACK® LJ300

Lumberjack® LJ300 has now been supplemented by two adjustable sleds, easily adjusted to pipe size.


The smaller sled is used in pipes with inner diameter ranging from 200 up to 375 mm (8"-15") and the larger sled for pipe 400 up to 700 mm (16"-28").




The sleds are equipped with interchangeable runner wheels for easier propulsion and service.

For the larger sled a special expander plate has been developed to reduce cutting chain length and therefore increase efficiency. See extended information "Expander Plate for LJ300".

The large sled (16"-28") can be supplied with extensions to stabilize the sled in pipe.

STÄLLBAR SLÄDE / ADJUSTABLE SLED



	LJ300-S8-S15	LJ300-S16-S28
	Ø 200-375 mm (8"-15")	Ø 400-700 (16"-28")
	430 x 185 mm	535 x 380 mm
	13 kg	21 kg

Reservdelar till ställbar släde / Spare parts for adjustable sled



100140



Chassi
Chassie



100140-004

Låsplåt
Locking plate



LJ300-S08-S15-SP02

Medar 200-375 mm
Runners 8"-15"



LJ300-S16-S28-SP02

Medar 400-700 mm
Runners 16"-28"



LJ300-S16-S28-SP03



Förlängning till med 400-700
Extension for runner 16"-28"



LJ300-S08-S15-SP01

Hjul Ø 45 mm (200-375 mm)
Wheel Ø 45 mm (8"-15")



LJ300-S16-S28-SP01

Hjul Ø 60 mm (400-700 mm)
Wheel Ø 60 mm (16"-28")

Kätting till expanderplatta / Cutting chain for expander plate



LJ-SP019



Ø 400 mm (16")



2

LJ-SP020

Ø 500 mm (20")

3.5

LJ-SP022

Ø 600 mm (24")

5.5

LJ-SP024

Ø 700 mm (28")

7.5

 Rördimension
Pipe dimension

 Vikt
Weight

 Antal länkar
No. of links

 Längd x Bredd
Length x Width